

Blue Magic Industrial Grade Pipe Thread Compound



For a "Positive Leak Proof Seal" on All Types of Threaded Connections Including CPVC



NSF Standard 14
NSF Standard 61



Underwriters' Laboratories of Canada Listed for Natural Gas, Gasoline, Petroleum Oils, Propane & Butane

PRESSURE RANGE USE:

Gases:
Up to 3,000 PSI (435 kPa)
Liquids:
Up to 6,000 PSI (870 kPa)

BLUE MAGIC is an all purpose, non-seizing, industrial grade pipe thread compound that produces a leak proof seal on all types of metal and plastic threaded connections.

BLUE MAGIC is a smooth, grit free, completely homogenized, blue industrial grade paste.

- Non-Separating
- Grit Free
- -50°F (-45°C) to +400°F (+204°C) Temperature Range
- Safe for PVC & CPVC
- Easy Cleanup
- Nontoxic
- Non Combustible

Suitable for use on systems carrying:

- | | | |
|---------------------|------------------|--------------------|
| Acids, Dilute | Coal Tar Naphtha | Hydrogen |
| Air, Compressed | Cutting Oils | Inert Gases |
| Alkalis, Dilute | Diesel Fuel Oil | Jet Fuel |
| Ammonia | Freons (All) | Kerosene |
| Aliphatic Solvents | Gasohol | Lacquer |
| Brine | Gasoline | L P Gases |
| Butane | Glycol | Mineral Oils |
| Carbon Dioxide | Heating Oils | Natural Gas |
| Castor Oils | Helium, Gaseous | Nitrogen Gas |
| Chlorinated Water | Hydraulic Oils | Petroleum Solvents |
| Propane | Steam Lines | Water, Potable |
| Refrigeration Gases | Sugar, Liquid | Soap, Liquid |
| | Vegetable Oils | |

FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin*, Zytel*, FlowGuard GOLD CPVC, Blazemaster** CPVC, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon***, Cycloc****, and all types of metal. Approved for SPEARS®, Thompson Plastics, & IPEX Fittings.**

Blue Magic Industrial Grade Pipe Thread Compound

BLUE MAGIC INDUSTRIAL GRADE PIPE THREAD COMPOUND

PRODUCT DESCRIPTION

PRODUCT

BLUE MAGIC Industrial Grade Thread Sealing Compound

DRYING TIME

The system may be pressurized immediately after assembly. Soft set, non-hardening.

TEMPERATURE RANGE USE

Gases: 50°F (-45°C) to 400°F (204°C)

Liquids: 50°F (-45°C) to 400°F (204°C)

Brushable to 50°F (-45°C)

ENVIRONMENTAL STATEMENT

BLUE MAGIC is formulated with non-toxic inert oils and is free from any lead containing ingredients.

CORROSIVENESS

BLUE MAGIC is non-corrosive, and prevents the corrosion and seizing of threads.

DIRECTIONS FOR USE

1. Stir well before using.
2. Brush liberally onto male threads
3. Make up joint in a normal manner

On large diameter pipe 4" (100 mm) and up, first wrap the pipe threads with two or more thicknesses of **tape-Unyte** PTFE tape, then apply **BLUE MAGIC** over the tape.

