

Large Bore "Gibault" Style Couplings

PEPEMATE LARGE BORE COUPLINGS



STRAIGHT COUPLING

**Sizes 345mm to
2200mm Available**

High Pressure Rating:

Pipemate standard coupling for sizes up to DN 700 have a suitable working pressure of 30 bar and for sizes DN 800 – DN 1200 are suitable for a working pressure of 25 bar.

Suitable for :

- * Ductile Iron Pipe
- * Cast Iron Pipe
- * Mild Steel Pipe
- * AC Pipe
- * PVC Pipe
- * Special model also suitable for PE Pipe

Features

- * Accepts minor misalignment in straight pipes.
- * FBE Coated.
- * High Pressure Rating.
- * Pipemate coupling joins pipe ends without heat (welding) damaging the coating.
- * The flexibility of the Couplings easily takes care of axial expansion and contraction.
- * Long radius curve bends can be laid without special bends.
- * Can be dismantled to enable quick repair or maintenance

Time saving installation. All you need is a spanner , no welding , generator or site joining equipment required.

**The standard coating is Fusion Bonded Epoxy Powder (FBEP), an extremely effective anti-corrosion coating .
Approx 200 microns thick.**

Sealing rings are natural rubber supplied as standard but EPDM, Nitrile and SBR are also available on request at extra cost.